Sea Foam Sales Company

P.O. Box 5178

Hopkins, MN 55343-1178

Phone (952)938-4811

MATERIAL SAFETY DATA INFORMATION

FOR



SEA FOAM DEEP CREEP Part No. DC-14

	NET WT 12 02 (340 g)		
====== SECTION I -	- IDENTIFICATION ====================================		
Deep Creep			
Sea Foam Formula: Prop	prietary Blend Date Prepared 4-1-2002		
EMERGENCY PHONE : (708) 598-710	00 Mfg. Code ID: L-12749		
======= SECTION II - HAZARDOU	US INGREDIENTS/SARA III INFORMATION =======		
DEDODEADIE COMPONENES	VAPOR PRESSURE WEIGHT		
REPORTABLE COMPONENTS	mm Hg @ TEMP PERCENT		
PALE OIL	.01 68 40-60%		
NAPHTHA	.01 68 40-60% 10 68 25-35%		
IPA	33 68 10-20%		
CARBON DIOXIDE	38650 60 3-5%		
*** No toxic chemical(s) subject to the reporting require	ements of section 313 of Title III and of 40 CFR 372 are present. ***		
======================================	YSICAL/CHEMICAL CHARACTERISTICS ==========		
BOTI.TNG BANGE: 177 deg E - 500 de	eg F SPECIFIC GRAVITY (H2O=1): 0.85		
	EVAPORATION RATE: SLOWER THAN ETHER		
SOLUBILITY IN WATER: NIL	EVAPORATION RATE: SLOWER THAN ETHER		
APPEARANCE AND ODOR: AEROSOL PROI			
APPEARANCE AND ODOR: AEROSOL PROL			
======= SECTION IV - FIRE AND EXPLOSION HAZARD DATA =========== FLASH POINT: 55 deg F METHOD USED: TCC			
		FLAMMABLE LIMITS IN AIR BY VOLUME	
		EXTINGUISHING MEDIA: FOAM, CO2, I	
SPECIAL FIREFIGHTING PROCEDURES			
	WATER MAY BE USED TO COOL CONTAINERS TO PREVENT		
	WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOO		
	AND SELF-CONTAINED BREATHING APPARATUS.		
UNUSUAL FIRE AND EXPLOSION HAZARI			
CLOSED CONTAINERS MAY EXPLODE FROM INTERNAL PRESSURE BUILD-UP WHEN EXPOSED TO EXTREM HEAT AND DISCHARGE CONTENTS. VAPOR ACCUMULATION CAN FLASH OR EXPLODE IF IGNITED. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT E READILY APPARENT. OBTAIN MEDICAL ATTENTION.			
		READILI APPARENI. OBIAIN MEDICAL	ATTENTION.
		======================================	N V - REACTIVITY DATA =========================
STABILITY: STABLE			
CONDITIONS TO AVOID			
APPLICATION TO HOT SURFACES. STORAGE ABOVE 120 DEG F. EXPOSURE TO OPEN FLAME.			
INCOMPATIBILITY (MATERIALS TO AVO			
STRONG OXIDIZING AGENTS.			
HAZARDOUS DECOMPOSITION OR BYPROI	DIICTS		
MAY PRODUCE FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE. HAZARDOUS POLYMERIZATION: WILL NOT OCCUR			
RAZARDOUS POLIMERIZATION: WILL NO	JI ULLUK		

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE RESPIRATORY IRRITATION, HEADACHE, NAUSEA, FATIGUE, DROWSINESS, IMPAIRED CO-ORDINATION. SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE SKIN: CONTACT MAY DRY THE SKIN; PROLONGED CONTACT MAY CAUSE MODERATE IRRITATION. EYES: LIQUID OR VAPOR CAN CAUSE MODERATE TO SEVERE IRRITATION. SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE NOT EASILY ABSORBED. SOLVENT ACTION CAN DRY AND DEFAT THE SKIN CAUSING THE SKIN TO CRACK, LEADING TO DERMATITIS. INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE NOT A LIKELY ROUTE OF EXPOSURE. IF SWALLOWED, DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ADVICE AND/OR ATTENTION. HEALTH HAZARDS (ACUTE AND CHRONIC) ACUTE: EYE IRRITANT. POSSIBLE SKIN IRRITANT. CHRONIC: NONE KNOWN. CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE NONE KNOWN. EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF NEEDED. APPLY ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. GET MEDICAL ATTENTION. SKIN: WIPE OFF WITH TOWEL. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. EYES: WASH IMMEDIATELY WITH LARGE VOLUMES OF FRESH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. CLEAN UP AREA WITH ABSORBENT MATERIAL AND PLACE IN CLOSED CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. BEFORE ATTEMPTING CLEAN UP, REFER TO OTHER SECTIONS OF THIS MSDS FOR HAZARD CAUTION INFORMATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE AND USE IN COOL, DRY, WELL-VENTILATED AREAS. DO NOT STORE ABOVE 120 DEG F. DO NOT PUNCTURE OR INCINERATE (BURN) CANS. DO NOT STICK PIN, NAIL OR ANY OTHER SHARP OBJECT INTO OPENING ON TOP OF CAN. DO NOT SPRAY IN EYES. DO NOT TAKE INTERNALLY. SEE PRODUCT LABEL FOR ADDITIONAL INFORMATION.

OTHER PRECAUTIONS

SMALL PRESSURIZED CONTAINERS OF FLAMMABLE PRODUCTS MAY BE STORED IN AREAS SUITABLE FOR ORDINARY COMBUSTIBLES WITH RESPECT TO CONSTRUCTION, DRAINAGE, CONTROL OF IGNITION SOURCES, AND VENTILATION EXCEPT THAT THEY SHOULD NOT BE STORED IN BASEMENTS.

RESPIRATORY PROTECTION

NONE UNDER NORMAL USE. AVOID BREATHING VAPORS. IN RESTRICTED AREAS, USE APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICLES AND VAPOR. IN CONFINED AREAS, USE APPROVED AIR LINE TYPE RESPIRATOR OR HOOD. SELF-CONTAINED BREATHING APPARATUS IS REQUIRED FOR VAPOR CONCENTRATIONS ABOVE PEL/TLV LIMITS.

VENTILATION

SUFFICIENT TO PREVENT INHALATION OF SOLVENT VAPORS. GENERAL DILUTION AND/OR LOCAL EXHAUST VENTILATION IN VOLUME OR PATTERN TO KEEP PEL/TLV OF MOST HAZARDOUS INGREDIENT BELOW ACCEPTABLE LIMIT AND LEL BELOW STATED LIMIT.

PROTECTIVE GLOVES

NONE UNDER NORMAL USE. SOLVENT RESISTANT REQUIRED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION

NONE UNDER NORMAL USE; HOWEVER, USE OF SAFETY GLASSES WITH SPLASH GUARDS OR FULL FACE SHIELD IS RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NONE UNDER NORMAL USE; HOWEVER, USE OF SOLVENT RESISTANT APRONS OR OTHER CLOTHING IS RECOMMENDED.

WORK/HYGIENIC PRACTICES

EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.