

Page 1 of 4 Updated 04-15-2002 Supersedes 9-27-01 MSDS# NOR480

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Superline 15W-40 Product description: Engine Oil/Lubricant

MANUFACTURER: Northland Products Company Chemtrec: 1-800-424-9300 1000 Rainbow Drive Waterloo, IA 50704

EMERGENCY TELEPHONE NUMBERS:

319-234-5585, 1-800-772-1724 _____

2. COMPOSITION/INFORMATION ON INGREDIENTS

	<u>wt. Percent</u>	<u>CAS Registry #</u>
Lube Oil Base Stock	75-82	064742-54-7
Petroleum Additives	18-25	Mixture

3. HAZARD IDENTIFICATION

Emergency Overview:

Clear, Amber, Liquid. (May be dyed or odormasked.) Health studies have shown that petroleum hydrocarbons pose potential human health risks which may vary from person to person. Exposure to liquids, mists, vapors and fumes should be minimized.

POTENTIAL HEALTH EFFECTS:

TNHALATTON:

Vapors are minimal under normal conditions but should be avoided, concentrations may reach levels that could cause slight irritation.

EYE CONTACT:

May cause slight temporary eye irritation. Corneal injury is unlikely. Vapors or mists may irritate eyes.

SKIN CONTACT:

May cause skin irritation. Discontinue use if irritation persists.

INGESTION:

Ingestion of oil may irritate the digestive tract and could cause diarrhea. Single dose oral toxicity is greater than 5000 mg/Kg in rats.

OTHER:

The TLV has not been determined for this material. The TLV for oil mists is 5 mg/cubic meter.


Hazardous Material Identification System (HMIS):

Health-1, Flammability-1, Reactivity-1 (Based on components) Superline 15W40





_____ 4. FIRST AID MEASURES INHALATION: Remove the victim from the area to fresh air. Call a physician. Give oxygen if victim is breathing hard. EYE CONTACT: Flush eyes with large amounts of water immediately for 15 minutes or until irritation subsides. If irritation persists, get medical attention. SKIN CONTACT: Wash affected areas thoroughly with soap and water. Remove contaminated clothing and wash them before wearing again. Call a physician if irritation persists. INGESTION: Call a doctor immediately. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. _____ 5. FIRE FIGHTING MEASURES Flash point: 350°F Minimum (COC)Flammable limits: Not Determined Autoignition Temperature: Not Available GENERAL HAZARD: May release vapors that form flammable mixtures when temperatures are at or above the flash point. Toxic gases will form upon combustion. FIRE FIGHTING INSTRUCTIONS: Either allow fire to burn out under controlled conditions or extinguish with foam, CO₂, or dry chemical. Try to cover liquid spills with foam. Shut off fuel to fire if possible to do so without hazard. FIRE FIGHTING EQUIPMENT: NIOSH approved self-contained breathing apparatus and eye protection are required for fire fighting personnel on all indoor fires and any significant outdoor fires. HAZARDOUS COMBUSTION PRODUCTS: Smoke, fumes, carbon monoxide, carbon dioxide and water. NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) Health-1, Flammability-1, Reactivity-1 (Based on components) -----6. ACCIDENTAL RELEASE MEASURES Notify the appropriate authorities immediately. Take all actions necessary to prevent adverse effects of the spill. Eliminate ignition sources. Shut off leak if safe to do so. Dike spilled liquid with sand/earth and dispose of properly. DO NOT use sawdust or other combustible materials. Prevent product from entering sewers or waterways. National Response Center 1-800-424-8802 Superline 15W40



7. HANDLING AND STORAGE

STORAGE TEMPERATURE: Ambient STORAGE PRESSURE: Atmospheric

GENERAL:

Keep container closed. Loosen closure cautiously before opening. Store in well ventilated area away from incompatible materials. (See Section 10) Keep away from heat, sparks and flames. Empty container may still retain hazardous properties.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Use mechanical ventilation to control vapor concentrations in confined spaces. General ventilation should be sufficient for most operations.

PERSONAL PROTECTION: Respirator: Use an air supplied respirator when concentrations are over the exposure limits. Protective Clothing: Wear rubber gloves, rubber boots, a chemical worker's suit and chemical splash goggles as appropriate.

9. PHYSICAL AND CHEMICAL PROPERTIES

Vapor pressure: Negligible at ambiantVapor density: Not determinedSolubility in water: NegligibleSpecific gravity: 0.90 approximatelypH: Not availableOdor: Petroleum (Could be masked)Appearance: Clear Amber (Could be dyed)Physical state: Liquid	
Physical state : Liquid	

10. STABILITY AND REACTIVITY

GENERAL: This product is stable and will not polymerize. INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID: If this product is overheated (especially in the presence of water) Hydrogen Sulfide may be released. (140°F Max Storage Temperature) HAZARDOUS DECOMPOSITION: Hydrogen Sulfide



Superline 15W40 Page 4 of 4

11. TOXICOLOGICAL INFORMATION

No component of this product present at levels greater than 0.1% is identified as a carcinogen by NTP, IARC or OSHA.

12. ECOLOGICAL INFORMATION

No data is available.

13. DISPOSAL CONSIDERATIONS

Ensure disposal is in compliance with Federal-State-Local laws. Do not landfill or dispose of in sink drains or sewers.

14. TRANSPORTATION INFORMATION

DOT (Department of Trans	sportation):
Proper shipping name	: Petroleum Lubricating Oil.
Hazard class	: Not regulated
Identification number	: Not regulated
Labeling	: Not regulated

15. REGULATORY INFORMATION

TSCA(Toxic Substance Control Act): All components of this product are listed on the U.S. TSCA inventory. CERCLA(Comprehensive Response Compensation, and Liability Act): This product is not subject to any special reporting under the requirements of CERCLA. We recommend you contact local authorities to determine local reporting requirements. SARA TITLE III(Superfund Amendments and Reauthorization Act): 311/312 Hazard Categories: This material is defined as hazardous by OSHA under 29 CFR part 1910.1200(d). 313 Reportable Ingredients: Contains 1.3 weight percent of Zinc compounds.

16. OTHER INFORMATION

THE INFORMATION PRESENTED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE DEPENDABLE AND IS ACCURATE TO THE BEST OF NORTHLAND PRODUCTS COMPANY'S KNOWLEDGE; HOWEVER, NORTHLAND PRODUCTS COMPANY MAKES NO WARRANTY WHATSOEVER, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. NORTHLAND PRODUCTS COMPANY ASSUMES NO RESPONSIBILITY FOR THE INJURY TO THE RECIPIENT OR TO THIRD PARTY PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.