

Material Safety Data Sheet

and Safe Handling and Disposal Information

Section 1. Chemical Product and Company Identification

Product name ZEP TIRELESS SHINE

Product Use Aerosol Tire Dressing

Product Code 0063

Date of issue 12/28/04 Supersedes 02/12/04

Emergency For MSDS Information:

Acuity Specialty Products Group, Inc. Telephone

Compliance Services 1-877-I-BUY-ZEP (428-9937) **Numbers**

For Medical Emergency

INFOTRAC:

(877) 541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency

CHEMTREC:

(800) 424-9300 - All Calls Recorded

In the District of Columbia (202) 483-7616

HMIS

1

4

0

B

Health

ire Hazard

Personal Protection

Reactivity

Prepared by Compliance Services Group

Acuity Specialty Products Group 1420 Seaboard Industrial Blvd.

Atlanta, GA 30318

Section 2. Composition. Information on Ingredients

Name of Hazardous Ingredients	CAS#	% by Weight	Exposure Limits
PROPRIETARY SOLVENT BLEND	Proprietary	70-80	OSHA PEL (United States). TWA: 500 ppm 8 hour(s). ACGIH TLV (United States). TWA: 50 ppm 8 hour(s).

Section 3. Hazards Identification

Printing date: 12/28/04

Acute Effects

Routes of Entry Dermal contact. Inhalation.

Skin

Hazardous in case of skin contact (irritant, permeator). Direct contact may cause irritation and redness. Skin inflammation is characterized by itching, scaling, or reddening. Prolonged

or repeated contact may dry skin and cause irritation.

Eyes

Hazardous in case of eye contact (irritant). Inflammation of the eye is characterized by

redness, watering, and itching.

Inhalation Hazardous in case of inhalation (lung irritant). Avoid breathing vapors or spray mists. Overexposure by inhalation may cause respiratory irritation. Can cause central nervous system depression. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Ingestion

Harmful if swallowed. Aspiration hazard if swallowed- can enter lungs and cause damage.

Vomiting increases risk of chemical pneumonia.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse health effects are lessened by following all prescribed safety precautions, including use of proper personal protective equipment.

Carcinogenic Effects

Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Chronic Effects

Over-exposure by inhalation or absorption can cause central nervous system depression. Prolonged skin contact may cause dermatitis with drying and cracking of skin. Repeated or prolonged exposure to the substance can produce damage to liver.

See Toxicological Information (section 11)

Section 4. First Aid Measures

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 **Eye Contact**

minutes, keeping eyelids open. Get medical attention.

Skin Contact Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. If irritation

persists, get medical attention.

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give Inhalation

oxygen. Get medical attention.

Aspiration hazard if swallowed- can enter lungs and cause damage. Do NOT induce vomiting unless Ingestion

directed to do so by medical personnel. If vomiting occurs, keep head lower than hips to help prevent aspiration. NEVER give an unconscious person anything to ingest. Get medical attention immediately.

Page: 1/3

Section 5. Fire Fighting Measures

Flash Point Closed cup: <-18°C (<0°F) Flammable Limits LOWER: 1.2% UPPER: 6.7%

(Tagliabue.)

Flammability Extremely flammable. (CSMA) Aerosol that may flashback.

Fire Hazard FLAMMABLE LIQUID AND VAPOR. Vapor may cause flash fire. Vapors may accumulate

in low or confined areas, travel considerable distance to source of ignition and flash back.

Container explosion may occur under fire conditions or when heated.

Fire-Fighting Procedures Use dry chemical or CO₂. Wear special protective clothing and positive

pressure, self-contained breathing apparatus. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

Section 6. Accidental Release Measures

Spill Clean up Large spills are unlikely due to packaging.

Section 7. Handling and Storage

Handling Extremely flammable liquid and vapor. Store and use away from heat, sparks, open flame, or any other ignition

source. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or spray mists. Use only with adequate

ventilation. Wash thoroughly after handling. Wash contaminated clothing before reusing.

Storage CONTENTS UNDER PRESSURE. Store and use away from heat, sparks, open flame, or any other ignition source.

Keep away from heat and direct sunlight. Keep container in a cool, well-ventilated area. Do not store above 120°F

(49°C). Do not puncture or incinerate. Keep out of the reach of children.

Section 8. Exposure Controls, Personal Protection

Personal Protection Protective Clothing (Pictograms)

Eyes Safety glasses.

Body Chemical resistant gloves. (Viton, Nitrile, Neoprene)

Respiratory Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne

concentrations of vapors below their respective threshold limit value. Wear appropriate respirator when ventilation is

inadequate. Approved/certified respirator with organic vapor cartridges.

Section 9. Physical and Chemical Properties

Physical State Liquid. (Aerosol.)

PH Solor Clear , Colorless.

Odor Hydrocarbon. (Slight.)

Boiling Point 143° C (290°F) InitialVapor Pressure Not determined.Specific Gravity0.73 (Water = 1)Vapor Density >1 (Air = 1)

Solubility Insoluble in cold water, hot water. Evaporation Rate Not determined.

VOC (Consumer) 70.9% 4.33 (lb/gal) 519 (g/l)

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Avoid contact with strong oxidizers, excessive heat, sparks or open flame.

Hazardous Polymerization Will not occur.

Hazardous Decomposition Products Carbon Dioxide, Carbon Monoxide and other organic materials. .

Section 11. Toxicological Information

Toxicity to Animals Proprietary Ingredient:

VAPOR (LC50): Acute: 3400 ppm 4 hour(s) [Rat].

Proprietary Ingredient:

ORAL (LD50): Acute: 4700 mg/kg [Rat].
DERMAL (LD50): Acute: 13000 mg/kg [Rabbit].

VAPOR (LC50): Acute: 22500 ppm 8 hour(s) [Rat (Male)]. 19000 ppm 8 hour(s) [Rat

(Female)].

Section 12. Ecological Information
Ecotoxicity
Not available.
Biodegradable/OECD
Not available.

Section 13. Disposal Considerations

Waste must be disposed of in accordance with federal, Waste Stream Code: D001

Information state and local environmental control regulations. Classification: - (Hazardous waste.)

Origin: - (RCRA waste.)

Consult your local or regional authorities.

Product Code 0063 Material Safety Data Sheet Product Name ZEP TIRELESS SHINE

Section 14. Transport Information

Proper shipping name Consumer Commodity

DOT Classification ORM-D **UN number** Not regulated.

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

Section 15. Regulatory Information

U.S. Federal Regulations SARA 313 toxic chemical notification and release reporting:

No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean air act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA inventory.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.